



# STANDARD SERIES

MAIDA STYLE NUMBER D58ZOV200RA00

MAIDA ITEM NUMBER 01-1221

**VARISTOR SPEC SHEET**

### Electrical Specifications

Continuous AC Voltage	20	VAC
Continuous DC Voltage	26	VDC
Maximum DC Leakage @ 26 VDC	200	uA
Low Varistor Voltage Limit	30	VDC
High Varistor Voltage Limit	36	VDC
Nominal Varistor Voltage	33	VDC
Current for Varistor Voltage	1	mA
Maximum Clamp Voltage	73	V
Maximum Clamp Voltage Test Current	1	A
Peak Current Rating (1 Pulse)	250	A
Peak Current Rating (2 Pulse)	125	A
Energy Rating (8X20us)	1.1	J
Energy Rating (10X1000us)	1.1	J
Typical Capacitance	1930	pF
Impulse Response Time	< 50	ns
Minimum Hipot of Coating	2500	VDC
Minimum I.R. of Coating	1000	MΩ
Current/Energy Derating Above 85°C	-2.5	%/°C

### Thermal Specifications

Minimum Operating Temperature	-40	°C
Maximum Operating Temperature	85	°C
Varistor Voltage Temperature Coeff	-0.05	%/°C
Minimum Storage Temperature	-50	°C
Maximum Storage Temperature	125	°C
Recommended Solder Temperature	260	°C
Recommended Reflow Temperature	260	°C

### Notes

### Physical Specifications

Lead Style	005N
X Nominal	0.2 in.
X Tolerance	0.04 in.
Y Nominal	0.054 in.
Y Tolerance	0.03 in.
Z Nominal	0.207 in.
Z Tolerance	0.04 in.
Lead Length Nominal	1.00 in.
Lead Length Tolerance	min. in.
d Nominal	0.025 in.
Wire Gauge	22 AWG
Minimum Marking	Z200-00UL
Nominal Disk Size	5 mm
D Maximum	0.298 in.
T Maximum	0.176 in.
H Maximum	0.423 in.
Coating Type	EPOXY



\* Contact Maida for a more detailed configuration drawing.

### Safety Agency Recognitions

UL 1449 File Number	E321173
- Tested to Type:	4
C-UL File Number	
CSA File Number	
VDE File Number	
SEV File Number	



**MAIDA DEVELOPMENT COMPANY**  
P.O. Box 3529  
Hampton, Virginia 23663  
Ph: (757) 723-0785 Fax (757) 722-1194

www.maida.com